

PROFESSIONAL FM TRANSCEIVER

## **Main Features**

Battery Save, CTCSS/DCS **Voice Prompt** 1500mAH Li-ion Battery Pack **Economical and Practical** Super Light Weight





1500mAH Li-ion CTCSS/DCS **Battery Pack** 





**VOX Transmit** 







## Main Features Battery Save, CTCSS/DCS

- Voice Prompt
- 1500mAH Li-ion Battery Pack
- Economical and Practical
- Super Light Weight

## **SPECIFICATION**

GENERAL	
Frequency Range	UHF: 400~480MHz
Operating Temperature	-20°C~+60°C
Frequency Combination	Phase lock frequency synthesize
Frequency Stability	±2.5ppm
Memory Channel	16 Channels
Working voltage	DC 3.7V
Antenna Impedance	50Ω
Operating Mode	Simplex of co-frequency or alien
	frequency
Dimension	97mm×57mm×30mm
Weight	200g (Include Battery Pack)

TRANSMIT PART		
RF Power	3W	
Modulate Mode (W/N)	16КФF3E,11КФF3E	
Max. Freq. Deviation (W/N)	<5K / <2.5KHz	
Remain Wave Radiation	<-60dB	
Transmitting Current	≤1300mA	
RECEIVE PART		
Sensitivity	<0.25µV(12dB SINAD)	
Squelch Sensitivity	<0.20µV	
Intermodulation Antijamming	50dB	
Audio Power output	500mW	
Receiving Current	≤100mA	
Squelch Standby	20mA	

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.